

# OMNIKEY® 302I USB Reader

## Portable Smart Card Reader

- ▶ **Plug and Play** - Designed to facilitate easy device installation with high quality drivers\* for all major PC operating systems
- ▶ **Readily Compliant** - Meets all relevant industry standards for smooth integration in PC environment
- ▶ **Portable Form Factor** – Unique size makes it an ideal reader for large-scale deployments and mass distribution
- ▶ **Suits Any Application** - Compatible with virtually any smart card and major PC operating systems



### **ACCESS** quality.

The OMNIKEY® 302I is a high-performance, USB smart card reader that features all the trusted performance of OMNIKEY readers in a new and smaller form factor. Compliant with all industry standards, this reader is compatible with virtually any contact smart card, operating system and a variety of applications. This handy USB reader is the ideal choice for large-scale deployments with any type of contact smart card or application software. The 302I can be easily distributed together with any smart card, including credit cards, e-ID cards or software for other applications.

- ▶ Meets major standards including ISO 7816, EMV 2000, Microsoft WHQL, USB CCID, PC/SC, HBCI (Home Banking Computer Interface) and PC-2001 Specification
- ▶ Usage within an application is based on standardized interfaces like PC/SC, OCF (Open Card Framework) or CT-API
- ▶ USB CCID support makes integration into an existing system the easiest ever, by connecting host and smart card reader without the need of additional drivers
- ▶ Attractive, small size fits in an envelope to distribute with smart card, credit card, e-ID card or software for online-banking or digital signature applications
- ▶ All major operating systems supported
- ▶ Meets GSA FIPS 201 requirements
- ▶ Supports high speed data transmission

\* For driver download, please visit [www.omnikey.com](http://www.omnikey.com).

# Specifications

<b>Base Model Number</b>	OMNIKEY® 3021
<b>Dimensions</b>	2.91" x 2.52" x 0.51" / 74 x 64 x 13mm
<b>Weight</b>	1.69 oz / 48 g
<b>Power supply</b>	Bus powered
<b>Operating temperature</b>	32°-131° F (0° - 55° C)
<b>Operating humidity</b>	10-90% rH
<b>HOST INTERFACE</b>	
<b>Host Interface</b>	USB 2.0 CCID <sup>1</sup> (also compliant with USB 1.1)
<b>Transmission speed</b>	12 Mbps (USB 2.0 full speed)
<b>SMART CARD INTERFACE</b>	
<b>Standards</b>	ISO 7816 & EMV <sup>2</sup> 2000 Level 1
<b>Protocols</b>	T=0, T=1, 2-wire: SLE 4432/42 (S=10), 3-wire: SLE 4418/28 (S=9), I <sup>2</sup> C (S=8)
<b>Card size</b>	ID-1 (full-size)
<b>Smart Card interface speed</b>	420 kbps (when supported by card)
<b>Smart Card clock frequency</b>	Up to 8 MHz
<b>Supported card types</b>	5V, 3V and 1.8V Smart Cards, ISO 7816 Class A, B and C
<b>Power to Smart Card</b>	60 mA
<b>Smart Card detection</b>	Movement detection with auto power-off / Automatic detection of smart card type/ Short circuit and thermal protection
<b>8 Pin Handling</b>	C4 / C8 supported
<b>Supported APIs</b>	PC/SC driver (ready for 2.01), CT-API (on top of PC/SC), Synchronous-API (on top of PC/SC), OCF (on top of PC/SC)
<b>PC/SC Driver Support</b>	Windows® 2000 / XP (32bit), 2003 Server, 2008 Server, Windows® CE 5.0 / CE.NET / CE 6.0 (depending on hardware), Windows® XP 64bit, Windows® Vista (32bit / 64bit), Windows 7 (32bit / 64bit), Linux®, Mac® OS X (Power PC/Intel)
<b>Embedded Technology</b>	OMNIKEY® Smart@Link Chipset
<b>Status indicator</b>	Blue LED
<b>Color</b>	Transparent/Silver
<b>Options</b>	<b>Customer Specific Logo, Label and Colors:</b> Available upon request
<b>Composition</b>	Poly carbonate
<b>Connector cable</b>	59.1" / 150 cm
<b>Durability</b>	100,000 insertions
<b>Meantime between failure (MTBF)</b>	500,000 hours
<b>Compliance / Certification</b>	Microsoft® WHQL <sup>3</sup> , EMV <sup>2</sup> 2000 Level 1, ISO 7816, HBCI <sup>4</sup> , USB 2.0 (USB 1.1 compatible), CCID1, GSA FIPS201 approved product list
<b>Safety / Environmental</b>	CE, WEEE, FCC, UL, VCCI, MIC, RoHS
<b>Warranty</b>	Two year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

1 = Chip Card Interface Device, 2 = Europay® MasterCard® Visa®, 3 = Windows® Hardware Quality Lab, 4 = Home Banking Computer Interface



**ACCESS** experience.

HID Global Offices:

**Corporate North America**  
15370 Barranca Pkwy  
Irvine, CA 92618  
U.S.A.  
Phone: (800) 237-7769  
Phone: +1 (949) 732-2000  
Fax: +1 (949) 732-2360

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Phone: +852 3160-9800  
Fax: +852 3160-4809

**Latin America**  
Circunvalacion Ote. #201 B  
Despacho 2  
Col. Jardines del Moral  
Leon 37160, Gto.  
Mexico  
Tel: +52 477 779 1492  
Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
Haverhill Business Park  
Phoenix Road  
Haverhill, Suffolk  
CB9 7AE  
England  
Phone: +44 (0) 1440 714 850  
Fax: +44 (0) 1440 714 840



© 2010 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 02/2010

MKT-OMNIKEY\_3021\_DS-EN

hidglobal.com