



OMNIKEY® 5321 CLi USB Reader

CONTACTLESS USB SMART CARD READER



- **Versatile Desktop Applications** – Ideal for end-user environments using contactless HID iCLASS® technology
- **Fast Contactless Transmission** – Supports fastest ISO standard transmission modes
- **Designed for User Convenience** – Housing design is optimized for advanced contactless applications
- **Readily compliant** – Seamless integration with HID on the Desktop™ and other applications

The OMNIKEY® 5321 CLi USB smart card reader represents the ideal contactless HID iCLASS® reader in a convenient desktop device. Reading and writing to any contactless HID iCLASS card, the device economically supports desktop clients where contactless iCLASS technology is used.

Utilizing contactless smart card technology for PC-linked applications, the OMNIKEY 5321 CLi allows users to experience the convenience, speed and security of HID iCLASS contactless technology for applications such as iCLASS on the Desktop™.

The OMNIKEY 5321 series readers work seamlessly with iCLASS-enabled logical access applications in combination with naviGO™ software, which is part of the HID on the Desktop solution. naviGO is a cost-effective solution that simplifies deployment of strong authentication managing and automating the life cycle of strong authentication user credentials on iCLASS smart cards. Designed to enable HID on the Desktop™, naviGO allows card holders to manage their own enrollment, PIN management and knowledge-based authentication through a self-service browser based application.

* For driver download, please visit www.omnikey.com.

FEATURES:

- Secure authentication device for logging on to PC or IT infrastructure
- Does not require organizations using iCLASS to re-badge, issue a new token or make any changes to their physical access control system
- Easy to install and can be used with naviGO software to converge access from the door to the logging onto PCs
- Compliant with all relevant safety and environmental standards, including CE, FCC, UL, RoHS and WEEE



SPECIFICATIONS

Base Model Number	OMNIKEY® 5321 CLI
Dimensions	3.78" x 3.07" x 0.31" (115 x 96.5 x 25.5 mm)
Weight	Approx. 5.64 oz (160 g)
Power Supply	Bus powered
Operating Temperature	32-131 °F (0-55 °C)
Operating Humidity	10-90% rH
HOST INTERFACE	
Host Interface	USB 2.0 (also compliant with USB 1.1)
Transmission Speed	12 Mbps (USB 2.0 full speed)
CONTACTLESS SMART CARD INTERFACE	
Protocols	HID iCLASS®
Driver Support	Windows 2000, Windows XP (32 bit / 64 bit), Windows 2003/2008 Server, Windows® CE 5.0 / 6.0 / CE.NET (depending on hardware), Windows® Vista (32 bit / 64 bit), Windows® 7 (32 bit / 64 bit), Linux ¹
Status Indicator	Dual color LED (green = ready, red = busy)
Color	Gray
Options	Customer-specific logo, label and colors: available upon request
Composition	ABS
Meantime Between Failure (MTBF)	500,000 hours
Compliance / Certification	Microsoft® WHQL ¹ , USB 2.0 (USB 1.1 compatible)
Safety / Environmental	CE, FCC, UL, RoHS, WEEE
Warranty	Two-year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

¹ = Windows® Hardware Quality Lab



North America: +1 949 732 2000
 Toll Free: 1 800 237 7769
 Europe, Middle East, Africa: +49 6123 791 0
 Asia Pacific: +852 3160 9800
 Latin America: +52 477 779 1492

ASSA ABLOY
 An ASSA ABLOY Group brand