

# OMNIKEY® 532I CLi USB Reader

## Contactless USB Smart Card Reader

- ▶ **Versatile Applications** – Ideal for end-user environments using contactless HID iCLASS® technology
- ▶ **Fast Contactless Transmission** – Supports fastest ISO standard transmission modes
- ▶ **Designed for User Convenience** – Housing design is optimized for advanced contactless applications
- ▶ **Readily compliant** – Seamless integration with iCLASS on the Desktop™ and other applications



### **ACCESS** quality.

The OMNIKEY® 532I CLi USB smart card reader represents the ideal contactless HID iCLASS® reader in a convenient desktop device. Reading and writing to any contactless HID iCLASS card, the device economically supports desktop clients where contactless iCLASS technology is used.

Utilizing contactless smart card technology for PC-linked applications, the OMNIKEY 532I CLi allows users to experience the convenience, speed and security of HID iCLASS contactless technology for applications such as iCLASS on the Desktop™.

The OMNIKEY 532I series readers work seamlessly with iCLASS-enabled logical access applications in combination with naviGO™, a cost-effective solution that simplifies deployment of strong authentication, managing and automating the lifecycle of strong authentication user credentials on iCLASS smart cards. Designed to enable iCLASS on the Desktop™, naviGO allows card holders to manage their own enrollment, PIN management and knowledge-based authentication through a self-service browser based application.

- ▶ Features host interface USB 2.0 and is compliant with USB 1.1
- ▶ Compliant with all relevant safety and environmental standards, including CE, FCC, UL, RoHS and WEEE

For actual driver downloads please visit [www.hidglobal.com/omnikey](http://www.hidglobal.com/omnikey)

# Specifications

<b>Base Model Number</b>	OMNIKEY® 5321 CLI
<b>Dimensions</b>	3.78" x 3.07" x 0.31" (115 x 96.5 x 25.5 mm)
<b>Weight</b>	Approx. 5.64 oz. (160 g.)
<b>Power supply</b>	Bus powered
<b>Operating temperature</b>	32°-131° F (0° - 55° C)
<b>Operating humidity</b>	10 - 90% rH
<b>HOST INTERFACE</b>	
<b>Host Interface</b>	USB 2.0 (also compliant with USB 1.1)
<b>Transmission speed</b>	12 Mbps (USB 2.0 full speed)
<b>CONTACTLESS SMART CARD INTERFACE</b>	
<b>Protocols</b>	HID iCLASS®
<b>Driver Support</b>	2000 / XP (32bit / 64bit), 2003/2008 Server, Windows® CE 5.0 / 6.0 / CE.NET (depending on hardware), Windows® Vista (32bit / 64bit), Windows® 7 (32bit / 64bit), Linux® (in preparation)
<b>Status indicator</b>	Dual color LED (green=ready, red=busy)
<b>Color</b>	Grey
<b>Options</b>	<b>Customer Specific Logo and Colors: Available upon request</b>
<b>Composition</b>	ABS
<b>Meantime between failure (MTBF)</b>	500,000 hours
<b>Compliance / Certification</b>	Microsoft® WHQL <sup>1</sup> , USB 2.0 (USB 1.1 compatible)
<b>Safety / Environmental</b>	CE, FCC, UL, RoHS, WEEE
<b>Warranty</b>	Two (2) year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

<sup>1</sup> = Windows® Hardware Quality Lab



© 2009 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 08/2009

MKT-OMNIKEY\_5321\_CLI\_DS\_EN Rev. 08/2009



**ACCESS** experience.

hidglobal.com

**HID Global Offices:**

**Corporate North America**  
 15370 Barranca Pkwy  
 Irvine, CA 92618  
 U.S.A.  
 Tel: 1 800 237 7769  
 Tel: +1 949 598 1600  
 Fax: +1 949 598 1690

**Asia Pacific**  
 19/F 625 King's Road  
 North Point  
 Island East  
 Hong Kong  
 Tel: +852 3160 9800  
 Fax: +852 3160 4809

**Latin America**  
 Circunvalación Ote. #201 B  
 Despacho 2  
 Col. Jardines del Moral  
 Leon 37160, Gto.  
 Mexico  
 Tel: +52 477 779 1492  
 Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
 Haverhill Business Park  
 Phoenix Road  
 Haverhill, Suffolk  
 CB9 7AE  
 England  
 Tel: +44 1440 714 850  
 Fax: +44 1440 714 840