



OMNIKEY® Smart@Link Reader Board Serial

ASSA ABLOY ITG, with its product brand OMNIKEY one of the world's leading manufacturers of innovative smart card readers, has developed a modern and state-of-the-art serial reader board optimized for evaluation purposes. The Reader Board Serial with its prominent connector pins provides the easy possibility to embed leading OMNIKEY contact smart card technology in a single device for OEMs.

Main Features:

- Driver platform identical to Smart@Link
- Unbranded OEM driver available
- Available with design-in manual
- PCB includes mounting holes
- Prominent connector pins for all relevant board contacts

Host Interface	
Host Interface	Serial (RS232 / TTL)
Transmission speed	115.200 kbps (Serial)
Power supply	PS/2 Keyboard adapter
Smart Card Interface	
Standards	ISO 7816 & EMV ² 2000 Level 1
Protocols	T=0, T=1, 2-wire: SLE 4432/42 (S=10), 3-wire: SLE 4418/28 (S=9), I ² C (S=8)
Card size	ID-1 (full-size)
Smart Card interface speed	420 Kbps (when supported by card)
Smart Card clock frequency	Up to 8 MHz
Supported card types	5V, 3V and 1.8V Smart Cards ISO 7816 Class A, AB and C
Power to Smart Card	60 mA
Smart Card detection	Movement detection with auto power-off / Automatic Detection of smart card type / Short circuit and thermal protection
8 Pin Handling	C4 / C8 supported
Other Features	
Status indicator	Green LED
Easy installation	Mounting screw holes on PCB
OEM driver	Unbranded driver available

Supported APIs	
PC/SC driver (ready for 2.01)	
CT-API (on top of PC/SC)	
Synchronous-API (on top of PC/SC)	
OCF (on top of PC/SC)	
I ² C (on top of PC/SC)	
PC/SC Driver Support	
Windows® 98 / ME, 2000 / XP (32bit), 2003 Server	
Windows NT 4	
Windows® CE 5.0 / CE.NET (depending on hardware)	
Windows® XP 64bit (AMD64, EM64T, IA64)	
Windows® Vista (32bit / 64bit)	
Linux®	
Embedded Technology	
CardMan Smart@Link Chipset	
Hardware Specifications	
Dimensions (LxWxH)	75 x 70 x 12 mm 3.0" x 2.6" x 0.47"
Weight with cable	75 gr / 2.65 oz
Operating temperature	0°-55°C / 32-131 °F
Operating humidity	10-90% rH
Connector cable	Ext. 180 cm / 70.9"
Durability	100.000 Insertions
Meantime between failure (MTBF)	500.000 hours
Compliance / Certification	
Microsoft® WHQL ³	CE
EMV ² 2000 Level 1	RoHS
ISO 7816	UL
HBCI ⁴	

1 = Chip Card Interface Device 2 = Europay® MasterCard® Visa® 3 = Windows® Hardware Quality Lab 4 = Homebanking Computer Interface

© ASSA ABLOY ITG reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. ASSA ABLOY ITG declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification. 29.08.2007- Page : 1 of 1

ASSA ABLOY Identification Technologies GmbH • Am Klingenberg 6A • 65396 Walluf, Germany • Tel: +49 6123 791 -0 • Fax: -110 • info@aaitg.com • www.aaitg.com

