

# Fargo DTC400e Card Printer/Encoder Specifications

<b>Print Method:</b>	Dye-Sublimation / Resin Thermal Transfer
<b>Resolution:</b>	300 dpi (11.8 dots/mm) continuous tone
<b>Colors:</b>	Up to 16.7 million / 256 shades per pixel
<b>Print Ribbon Options:</b>	<ul style="list-style-type: none"> <li>• Full-color with resin black and overlay panel, YMCKO*, 250 prints</li> <li>• Full-color half-panel with resin black and overlay panel, YMCKO*, 350 prints</li> <li>• Full-color with two resin black panels and overlay panel, YMCKOK*, 200 prints</li> <li>• Full-color with fluorescing, resin black and overlay panel, YMCKFO*, 200 prints</li> <li>• Dye-sublimation black and overlay panel, BO*, 500 prints</li> <li>• Resin black, and overlay panel, KO, 500 prints</li> <li>• Resin black, green, blue, red, white, 1,000 prints; silver and gold, 500 prints</li> </ul>
<b>Print Speed:*</b>	<ul style="list-style-type: none"> <li>• 7 seconds per card (K)*</li> <li>• 12 seconds per card (KO)*</li> <li>• 27 seconds per card (YMCKO)*</li> <li>• 35 seconds per card (YMCKOK)*</li> </ul>
<b>Accepted Standard Card Sizes:</b>	<ul style="list-style-type: none"> <li>• CR-80 (3.375"L x 2.125"W / 85.6mmL x 54mmW)</li> <li>• CR-79 Adhesive Back (3.313"L x 2.063"W / 84.1mmL x 52.4mmW)</li> </ul>
<b>Print Area:</b>	<ul style="list-style-type: none"> <li>• CR-80 edge-to-edge (3.36"L x 2.11"W / 85.3mmL x 53.7mmW)</li> <li>• CR-79 (3.3"L x 2.04"W / 83.8mmL x 51.8mmW)</li> </ul>
<b>Accepted Card Thickness:</b>	.009" – .040" / 9 mil – 40 mil / .229mm – 1.016mm
<b>Accepted Card Types:</b>	PVC or polyester cards with polished PVC finish; monochrome resin required for 100% polyester cards; optical memory cards with PVC finish
<b>Input Hopper Card Capacity:</b>	100 cards (.030" / .762mm)
<b>Output Hopper Card Capacity:</b>	Up to 30 cards (.030" / .762mm)
<b>Reject Hopper Card Capacity:</b>	15 cards (.030" / .762mm)
<b>Card Cleaning:</b>	Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon change
<b>Memory:</b>	2MB RAM
<b>Software Drivers:</b>	Windows 2000 / XP / Vista (32 and 64 bit) / Server 2003; Linux***
<b>Interface:</b>	USB 1.1 (USB 2.0 compatible), optional Ethernet with internal print server
<b>Operating Temperature:</b>	65° to 80° F / 18° to 27° C
<b>Humidity:</b>	20 – 80% non-condensing
<b>Dimensions:</b>	<ul style="list-style-type: none"> <li>• Single-Sided: 7.9"H x 13.62"W x 8.14"D / 201mmH x 346mmW x 207mmD</li> <li>• Dual-Sided: 7.9"H x 18.28"W x 8.14"D / 201mmH x 464mmW x 207mmD</li> </ul>
<b>Weight:</b>	<ul style="list-style-type: none"> <li>• Single-Sided: 8 lbs. / 3.63 kg</li> <li>• Dual-Sided: 11.55 lbs. / 5.22 kg</li> </ul>
<b>Agency Listings:</b>	<ul style="list-style-type: none"> <li>• Safety: UL 60950-1, CSA C22.2 (60950-1), and CE</li> <li>• EMC: FCC Class A, CRC c1374, CE (EN 55022 Class A, EN 55024)</li> </ul>
<b>Supply Voltage:</b>	100-240 VAC, 3.3 A
<b>Supply Frequency:</b>	50 Hz / 60 Hz
<b>Warranty:</b>	<ul style="list-style-type: none"> <li>• Printer – Two years including free loaner printer in the first year (U.S. only); optional Extended Warranty</li> <li>• Printhead – Two years, unlimited pass with UltraCard™ Cards</li> </ul>
<b>Fargo Materials:</b>	Fargo Card Printer/Encoders require highly specialized media to function properly. To maximize printed card quality and durability, printhead life and printer/encoder reliability, use only Fargo materials. Fargo warranties are void, where not prohibited by law, when non-Fargo materials are used.
<b>Encoding Options:</b>	<ul style="list-style-type: none"> <li>• ISO and Raw Binary Magnetic Stripe encoding, dual high- and low-coercivity, Tracks 1, 2, and 3</li> <li>• JIS II Magnetic Stripe encoding</li> <li>• Contact Smart Card Docking Station</li> <li>• Contactless Smart Card Encoder (HID® iCLASS®, MIFARE® and MIFARE DESFire)</li> <li>• Contact Smart Card Encoder reads from and writes to all ISO7816-1/2/3/4 memory and microprocessor smart cards (T = 0, T = 1) as well as synchronous cards</li> <li>• Prox Card Reader (HID read-only)</li> </ul>
<b>Options:</b>	<ul style="list-style-type: none"> <li>• Dual-sided Printing Module – Field-upgradeable</li> <li>• Magnetic Stripe Encoding Module – Field-upgradeable</li> <li>• Smart Card Encoding Modules – Field-upgradeable by technician</li> <li>• Printer cleaning kit</li> <li>• Ethernet networking with internal print server (replaces USB connection)</li> <li>• 100-card output hopper with or without reject tray</li> </ul>
<b>Software:</b>	Fargo Workbench Diagnosis Utility

\* Indicates the ribbon type and the number of ribbon panels printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, O=Overlay.

\*\* Print speed indicates an approximate print speed and is measured from the time a card drops into the output hopper to the time the next card drops into the output hopper. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is dependent on the size of the file, the CPU, amount of RAM and the amount of available resources at the time of the print.

\*\*\* Linux versions: Ubuntu 7.10, Red Hat Enterprise Desktop 5, Fedora Core 7, Fedora Core 8, openSUSE 10.3, Novell SUSE 10.

This data sheet is for informational purposes only. HID Global makes no warranties, expressed or implied, in this summary. Company and product names and data used in sample output are fictitious. Specifications are subject to change without notice. Fargo and Asure ID are registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. This is not an offer of sale. © 2008, HID Global Corporation. All rights reserved. REV09B



## ACCESS experience.

fargo.hidglobal.com

### HID Global Offices:

**Card Issuance Center of Excellence**  
6533 Flying Cloud Drive  
Eden Prairie, MN 55344  
U.S.A.  
Phone: 1 800 459 5636  
Phone: + 1 952 941 9470  
Fax: + 1 952 941 7836

**Corporate North America**  
15370 Barranca Pkwy  
Irvine, CA 92618  
U.S.A.  
Phone: 1 800 237 7769  
Phone: + 1 949 732 2000  
Fax: + 1 949 732 2360

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Phone: +852 3160 9800  
Fax: +852 3160 4809

**Latin America**  
Circunvalación Ote. #201 B  
Despacho 2  
Col. Jardines del Moral  
Leon 37160, Gto.  
Mexico  
Phone: +52 477 779 1492  
Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
Haverhill Business Park  
Phoenix Road  
Haverhill, Suffolk  
CB9 7AE  
England  
Phone: +44 1440 714 850  
Fax: +44 1440 714 840