

iCLASS® 13.56 MHz Contactless – Credentials



	iCLASS Clamshell	iCLASS Card	iCLASS Composite Card	iCLASS Card Embeddable	iCLASS Card Embeddable Composite	iCLASS Prox	iCLASS Prox Composite	iCLASS Prox Embeddable	iCLASS Prox Embeddable Composite	iCLASS Wiegand	iCLASS Wiegand Composite	iCLASS Key	iCLASS Tag
Base Part Number	2080	200X	210X	201X	211X	202X	212X	203X	213X	204X	214X	205X	206X
Read Range: *													
R10/RW100	Up to 2.5" (6.3 cm)		Up to 3.25" (8.2 cm)						Up to 3.0" (7.6 cm)			1.5" (3.8 cm)	
R30/RW300	Up to 3.0" (7.6 cm)		Up to 4.0" (10.1 cm)						Up to 3.00" (7.6 cm)			2.0" (5.0 cm)	
R40/RW400	Up to 4.5" (10.2 cm)		Up to 4.25" (10.8 cm)						Up to 4.5" (11.4 cm)			2.0" (5.0 cm)	
RK40/RK400	Up to 4.0" (8.9 cm)		Up to 3.5" (8.9 cm)						Up to 2.5" (6.3 cm)			2.0" (5.0 cm)	
Memory Size/ Application Areas	2k bits with 2 areas		2k bits with 2 application areas; 16k bits with 2 application areas (16k/2); 16k bits with 16 application areas (16k/16); 32k bits (16k/2+16k/1); 32k bits (16k/16+16k/1)										
HID Proximity 125 kHz	No					Yes					No		
Contact Smart Chip Module Embeddable	No			Yes			No			Yes			
Wiegand Strip	No									Yes		No	
Magnetic Stripe	No		Optional									No	
Printable **	Yes											No	
Slot Punch	Vertical Included		Vertical Optional						Horizontal or Vertical Optional			Key Ring Hole	No
Visual Security Options	N/A		Yes									N/A	
Warranty	Lifetime												

* Dependant upon installation conditions.

** Some types of printing processes can take these credentials out of ISO compliance for thickness. Consult factory for more information.