

AKB500 Keyboard

With Integrated MSR and OCR Functionality



COMPACT FOOTPRINT

The AKB500 keyboard integrates optical character recognition (OCR) and magnetic swipe readers (MSR) functionality to deliver a solid, multi-function device with a compact footprint that quickly establishes customer identity. It is ideal for airline passenger check-in and card reading, retail/point of sale (POS) terminals and security environments.

BIDIRECTIONAL READING

One of the key features of the AKB500 family is the placement of the read camera at the center of the read slot, allowing for bidirectional reading within the footprint of the device and saving valuable desk space.

SIMPLE FIRMWARE UPGRADES

The keyboard can be adapted to add a new host or to support non-standard cards, such as loyalty or frequent flyer and special dedicated formats. To ensure flexibility for the future, new firmware to add and modify features can be downloaded to the unit.


APPLICATIONS

- Check-In Counters
- Boarding Gates
- Retail / POS
- Security

FEATURES:

- Standard Layouts - 104-key US or 105-key European standard versions
- Reliable - Cherry mechanical key switches rated at 50 million operations
- Robust - Rugged design with steel chassis
- Flexible - Virtual serial RS-232 or keyboard wedge modes and an auxiliary RS-232 Port
- OCR Reader - Reads MRTD including passports & visas conforming to ICAO 9303 as well as ID, resident alien & green cards
- Magnetic Swipe Reader - Accepts ISO 1-, 2- & 3-track credit cards to ISO7811/2-5
- Options Including - Pointing device, left & right 'mouse' selection buttons, USB hub to connect USB mice and fingerprint scanner

AKB500 Keyboard



FEATURES

Connection Types

- USB *
- RS232

Technology

- OCR / MRZ
- Magnetic Strip

Reader Size

- Swipe

* Optional

AKB500 Keyboard

| READING CAPABILITIES | |
|--|---|
| OCR (Optical Character Recognition) | Standard OCR fonts: OCR-B Machine readable passports (MRP) : 2 lines of 44 characters Machine readable visas (MRV) : 2 lines of 44 characters, 2 lines of 36 characters Travel documents: 2 lines of 36 characters, 3 lines of 30 characters |
| MSR (Magnetic Stripe Reading) | Processing time: Manual swipe processing/read less than 1 second Card type: magnetic cards per ISO7810, ISO7811, AAMVA and custom data Read capability: magnetic stripe 1-, 2- or 3-track of low or high coercivity (300-4000 Oe) Swipe speed: 5 to 55 inches/second Magnetic head life: >500,000 swipes Read error rate: < 0.5% |
| ELECTRONIC | |
| Power Supply | +5 VDC <350 mA |
| Host interface | USB 2.0; full-speed, Keyboard Emulation, RS232 Serial |
| USB ports (optional) | Bus powered USB 2.0 hub (Full Speed) ports (max. load 100 mA per port) |
| Auxiliary RS-232 port interface | Bidirectional RS-232 by 9-way D-type |
| PHYSICAL | |
| Dimensions | 17 x 8 x 2 in (439 x 197 x 50 mm) |
| Colour | Dark Grey (Option for White) |
| Weight | 4 lbs. (1750g) |
| Cable length | 7 ft (2m) |
| THERMAL (AIR) | |
| Temperature | Operating 32°F to 122°F (0°C to 50°C) |
| Storage | -4°F to 140°F (-20°C to 60°C) |
| APPROVALS | |
| | Safety: EN 60950-1 EMC: FCC 47CFR Part 15/Sub-part B/Class A; EN 55022 Class B; EN 55024 Air IT: EASE™ Amadeus: ACUS™ ARINC iMuse & vMuse® Edge-airport: Airport Manager Cupp-T™ (P) RESA CREWS® (P) SABRE EGR® SITA CUTE® AirportConnect TravelSky 'Angel Cue'® Ultra CUSE® (P = Pending) |

To learn more, please contact us at: access-is@hidglobal.com



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108

For more global phone numbers click here

© 2022 HID Global Corporation/ASSA ABLOY AB. All rights reserved.
2022-02-15-eat-akb500-keyboard-ds-en PLT-06254

Part of ASSA ABLOY