

Glass Tag

Safe, reliable, effective RFID tags for pets, livestock and lab animals



Glass Tag contactless RFID transponders help manage and safeguard animals. In tag production, HID employs fully automated processes to ensure consistent quality and reliability. Patented direct-bonding technology enables more compact tag designs and optimized read ranges, delivering exceptional size to performance ratios.

Standard Glass Tag units are enclosed in biocompatible glass, making them harmless to animals. The optional parylene coating improves and accelerates tissue adhesion, preventing the movement of tags implanted subcutaneously.

Veterinary professionals trust HID quality transponders for implantation. Glass Tag units perform reliably over the long term, minimizing the potential for traumatic tag removal and replacement procedures. The variety of sizes available from HID ensures a tag to fit any animal: from fish and small mammals, to cats and dogs, to goats, sheep and horses.

Glass Tag devices help optimize livestock production and productivity, allowing individualized management, monitoring and feed control through each animal's lifecycle.

Larger HID Glass Tag transponders are ideal for cattle, sheep and goats, and are compatible with a choice of minimally invasive tagging options, including:

- Housing each glass tube in a ceramic bolus for easy insertion through the gullet
- Embedding it in a custom housing, such as a one-piece ear tag, or bird ring
- Inserting it into the animal in an injectable format

For tracking of birds, small Glass Tag RFID tags are embeddable in bird rings or bands.

HID Glass Tag Mini and Ultra transponders deliver greater read range than any low frequency tags of comparable size. Improved read range reduces animal stress by increasing the distances between animals, reader equipment, and operators. In kind, these tags reduce stress on system operators as well.



KEY BENEFITS:

- Unsurpassed quality – fully automated manufacturing and direct-bonding technology ensure tag reliability
- Optimum operation – the highest out-of-box performance ratings in the industry, with no line-of-sight requirements
- Comprehensive portfolio – choose from a broad range of standard sizes and integrated chips, or customize to fit any application







TECHNOLOGY HIGHLIGHTS:

- ISO 11784 and 11785 compliant
- Multiple IC options, including EM4305, Hitag S, FDX, HDX, Unique
- Bioglass capsules with parylene coating ensure optimal biocompatibility
- Unlimited resistance to water and chemical absorption
- Memory storage up to 2048 bits
- Custom sizes and programming available

Glass Tag



HID can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.

	Glass Tag					
	Unique	Mini		EM4305		
	12 mm	8 mm	10 mm	12 mm	22 mm	34 mm
						
Base Model Number	601201	684290	684210	684230	684250	684260
ELECTRONIC						
Operating Frequency	125 kHz	134.2 kHz				
Chip Type	Unique	EM4305		EM4305		
Memory	64 bit read-only	512 bit EEPROM		512 bit EEPROM		
Reading Distance	Dependent upon reader, environment and application					
PHYSICAL						
Dimensions	Ø 0.08 x 0.47 in (Ø 2.12 x 12 mm)	Ø 0.05 x 0.31 in (Ø 1.4 x 8 mm)	Ø 0.05 x 0.39 in (Ø 1.41 x 10 mm)	Ø 0.08 x 0.47 in (Ø 2.12 x 12 mm)	Ø 0.16 x 0.87 in (Ø 4 x 21.7 mm)	Ø 0.16 x 1.34 in (Ø 4 x 34.4 mm)
Tagging Method	Subcutaneous				External housing	
Housing Material	Bioglass					
CHEMICAL AND MECHANICAL						
Water	IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h					
Withstands Exposure To	Alcohol, ammonium chloride 25%, fuel B, HCL 10%, salt water					
Environmental Test Conditions	68° F (20° C), 100 h					
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]					
Shock	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]					
THERMAL						
Storage	-40° to +194° F (-40° to +90° C), 1000 h					
Operating	-13 °to +185° F (-25° to +85° C)					
Peak	248° F (120° C), 100 h; 284° F (140° C), 10 h					
OTHER						
Standards		ISO 11784, ISO 11785 (FDX-B)				
Options	Parylene coating (when ordering coating, increase base model number by one), custom programming					
Box Size	5.000 pcs. for GT Mini 2.000 pcs. for all GT 12mm, 12.5, 13, 22 and 22.5 mm 3.000 pcs. for all GT 9mm 300 pcs. for all GT 34 mm					
Warranty	2 Years					



ANIMAL IDENTIFICATION:

- **Companion animals**










- Cats
- Dogs
- Horses

- **Livestock**

- Cattle
- Goats
- Sheep

- **Laboratory and exotic animals**

- Ferrets
- Fish
- Mice and rats
- Pigeons

	Glass Tag								
	Ultra		HDX		Hitag S				
	9 mm	12.5 mm	22.5 mm	32 mm	12 mm		15 mm	22 mm	34 mm
									
Base Model Number	628230	684280	6B7250	6B7260	623230	624201	623242	623250	623260
ELECTRONIC									
Operating Frequency	134.2 kHz								
Chip Type	EM4305		HDX		Hitag S				
Memory	512 bit EEPROM		128 bit OTP		256 bit EEPROM	2048 bit EEPROM	256 bit EEPROM		
Reading Distance	Up to 35% greater than standard tag of same size		Dependent upon reader, environment and application						
PHYSICAL									
Dimensions	Ø 0.08 x 0.35 in (Ø 2.12 x 9 mm)	Ø 0.08 x 0.49 in (Ø 2.12 x 12.5 mm)	Ø 0.15 x 0.88 in (Ø 3.85 x 22.5 mm)	Ø 0.15 x 1.26 in (Ø 3.85 x 32 mm)	Ø 0.08 x 0.47 in (Ø 2.12 x 12 mm)		Ø 0.12 x 0.59 in (Ø 3.15 x 15.5 mm)	Ø 0.16 x 0.87 in (Ø 4 x 21.7 mm)	Ø 0.16 x 1.34 in (Ø 4 x 34.4 mm)
Tagging Method	Subcutaneous		External housing		Subcutaneous			External housing	
Housing Material	Bioglass								
CHEMICAL AND MECHANICAL									
Water	IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h								
Withstands Exposure To	Alcohol, ammonium chloride 25%, fuel B, HCL 10%, salt water								
Environmental Test Conditions	68° F (20° C), 100 h								
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]								
Shock	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]								
THERMAL									
Storage	-40° to +194° F (-40° to +90° C), 1000 h								
Operating	-13 °to +185° F (-25° to +85° C)								
Peak	248° F (120° C), 100 h; 284° F (140° C), 10 h								
OTHER									
Standards	ISO 11784, ISO 11785 (FDX-B)		ISO 11784, ISO 11785 (HDX)		ISO 11784, ISO 11785 (FDX-B)				
Options	Parylene coating (when ordering coating, increase base model number by one), custom programming								
Box Size	5,000 pcs. for GT Mini 2,000 pcs. for all GT 12mm, 12.5, 13, 22 and 22.5 mm 3,000 pcs. for all GT 9mm, 1,000 pcs. for all GT 32 mm 300 pcs. for all GT 34 mm								
Warranty	2 Years								



For further information, contact tagsales@hidglobal.com





hidglobal.com

North America: +1 512 776 9000

Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800

Latin America: +52 (55) 9171-1108

For more global phone numbers click here

© 2022 HID Global Corporation/ASSA ABLOY AB.
All rights reserved.

2022-03-28-idt-rfid-aid-glass-tag-family-ds-en
PLT-00002

Part of ASSA ABLOY