

Indala® Prox I25 kHz Proximity – Readers



Wallswitch Readers

Classic Readers

Mullion (Slim) Readers

Mid-Range Readers

Long-Range Reader

Heavy-Duty PinProx Keypad Readers

Membrane Keypad Readers

Base Model Number	603 Core Module FP-0500A		610 Core Module FP-0200A and FP-0200S (Serial)		620 Core Module ASR-620XX	FP5071B Black or FP5077B Beige	FP5061B - Black, 8-bit burst/buffered FP5067B - Beige, 8-bit burst/buffered FP5061M - Black, 3x4 matrix FP5067M - Beige, 3x4 matrix
Dimensions	Arch 4.5" x 3.0" x 0.8" (11.5 cm x 7.5 cm x 2.0 cm) Wave 5.5" x 3.3" x 1.1" (14.0 cm x 8.5 cm x 3.0 cm) Curve 5.0" x 3.8" x 1.1" (12.5 cm x 9.5 cm x 3.0 cm) Linear 4.6" x 3.0" x 0.9" (11.5 cm x 7.5 cm x 2.5 cm)	2.3" x 5.3" x 0.8" (6.0 cm x 13.5 cm x 2.0 cm)	Arch 4.5" x 1.7" x 0.8" (11.5 cm x 4.5 cm x 2.0 cm) Wave 5.5" x 1.7" x 1.1" (14.0 cm x 4.5 cm x 3.0 cm) Curve 4.9" x 1.7" x 1.1" (12.5 cm x 4.5 cm x 3.0 cm) Linear 5.5" x 1.7" x 0.8" (14.0 cm x 4.5 cm x 2.0 cm)	5.0" x 5.0" x 1.0" (12.5 cm x 12.5 cm x 2.5 cm)	11.2" x 11.2" x 1.8" (28.5 cm x 28.5 cm x 4.5 cm)	4.7" x 2.9" x 1.1" (12.0 cm x 7.5 cm x 3.0 cm)	4.5" x 3.0" x 0.7" (11.5 cm x 7.5 cm x 1.5 cm)
Weight Range	5.05-5.84 oz (143-166 g)	5.12 oz (145 g)	4.94-5.84 oz (140-166 g)	14.16-15.28 oz (401-433 g)	47.04 oz (1.33 kg)	13.44 oz (381.02 g)	7.08 oz (200.58 g)
Read Range	Up to 5.0" (12.5 cm)			Up to 12.0" (30.5 cm)	Up to 26.0" (66.0 cm)	Up to 4.0" (10.0 cm)	
Mounting	Single-gang electrical box	Replaces HID Classic Wiegand Swipe reader	Mullion	Single or double gang box	Non-ferrous wall surface (or use 3.0" spacer on or near ferrous surface)	Single-gang electrical box	
Power Supply	4-16 VDC				12-24 VDC	4-16 VDC	
Current Requirements	65 mA			117 mA	1.0A/750 mA	75 mA	
Termination	Pigtail				Terminal Strip	Pigtail	
Output Formats	Wiegand, Clock-and-Data, Serial TTL (requires use of BIL 232/422 Module)				Wiegand, Clock-and-Data	Wiegand, Clock-and-Data, Serial TTL (requires use of BIL 232/422 Module)	
Tamper					No		
Indoor/Outdoor					Both		
Warranty					Lifetime		