



**Next-Generation High-Frequency Contactless Smart Card  
PVC Cards 300X • Composite PVC/PET cards 305X**

- **Supports Secure Identity Object™ (SIO)** – Multi-layered security beyond the card technology, providing added protection to identity data.
- **Trusted Identity Platform® (TIP™) enabled** – Provides trusted identity within a secure ecosystem of interoperable products.
- **Supports future growth** – iCLASS® 13.56 MHz read/write contactless smart card technology with multiple, securely separated files enables multiple applications for future growth.
- **Flexible configurations** – Available in 2k bit, 16k bit or 32k bit with ability to add a magnetic stripe/barcode and anti-counterfeiting features (custom artwork and photo ID).

**HID Global SIOs deliver three key benefits: portability, security and extensibility.**

- SIOs are defined using open standards that can support any piece of data, including data for access control, biometrics, PC logon, and many other applications.

Building on the success of the flagship iCLASS standard for 13.56 MHz contactless smart card technology, HID Global's new access control platform goes beyond the traditional smart card model to offer a secure, standards-based, technology-independent and flexible identity data structure based on Secure Identity Object (SIO), a new HID portable credential methodology.

iCLASS SIO-Enabled (iCLASS SE) smart cards are part of the next-generation iCLASS SE access control platform and open ecosystem based on HID's Trusted Identity Platform (TIP) architecture for advanced applications, mobility and heightened security. iCLASS was specifically designed to make access control more powerful, more versatile, and more secure, with encryption for all

radio frequency data transmission between the credential and reader using a secure algorithm. iCLASS SE extends this technology by providing additional key diversification, authentication, encryption and portability for advanced security and performance.


HID's iCLASS SE 13.56 MHz read/write contactless smart card technology can be used for diverse applications such as physical access control, PC logon, biometric verification, time and attendance, cashless vending, public transportation, airline ticketing and customer loyalty programs..

### iCLASS SE<sup>®</sup> SMART CARD TECHNOLOGY FEATURES

- 13.56 MHz read/write contactless smart card technology for high-speed, reliable communications with high data integrity.
- Meets ISO 15693 for contactless communications.
- Proven Technology - Offers consistent read range not affected by body shielding or variable environmental conditions.
- Multiple securely separated application areas are each protected by 64-bit diversified read/write keys that allow complex applications and provide for future expansion.
- Durability - Passive, no-battery design allows for an estimated minimum 100,000 reads. Strong, flexible, and resistant to cracking and breaking.
- Ordering Options - Magnetic stripe, external card numbering, custom artwork and contact smart chip module.
- Photo ID Compatible - Print directly to the card with a direct image or thermal transfer printer.

### HIGHER SECURITY

- Trusted Identity Platform (TIP) Enabled - Provides trusted identity within a secure ecosystem of interoperable products.
- Multi-Layered Security - Ensures data authenticity and privacy through the multi-layered security of HID's SIO.
- SIO Data Binding - Inhibits data cloning by binding an object to a specific credential.
- Mutual authentication, encrypted data transfer, and 64-bit diversified keys for read/write capabilities.
- Expanded iCLASS Elite™ Program - Extends private security by protecting uniquely keyed credentials, SIOs and programming update keys.



## SPECIFICATIONS

	PVC	Composite	Technology
<b>Base Part Number</b>	3000	3050	2k bit (256 Bytes) card
	3001	3051	16k bit (2k Bytes) card with 2 application areas
	3002	3052	16k bit (2k Bytes) card with 16 application areas
	3003	3053	32k bit (4k Bytes) 16k/2+16k/1
	3004	3054	32k bit (4k Bytes) 16k/16 + 16k/1
<b>Configurations</b>	Available in 2k bit (256 Bytes), 16k bit (2K Bytes) or 32k bit (4K Bytes) configurations.		
<b>*Card Construction</b>	Thin, flexible polyvinyl chloride (PVC) laminate, and Composite PVC/PET		
<b>Dimensions</b>	2.127" x 3.375" x 0.033" max. (5.40 x 8.57 x 0.084 cm)		
<b>Weight</b>	0.20oz (5.7 g)		
<b>Operating Temperature</b>	300X PVC Cards: -40 to 122°F (-40 to 50°C) 305X Composite Cards: -40 to 158°F (-40 to 70°C)		
<b>Operating Humidity</b>	5-95% non-condensing		
<b>Operating Frequency</b>	13.56 MHz		
<b>Transaction Time</b>	<100 ms typical		
<b>Baud Rate</b>	15693 mode - 26 kbps		
<b>Memory Type</b>	EEPROM, read/write		
<b>Multi-application Memory</b>	2k bit (256 Bytes) card - 1 application area 16k bit (2k Bytes) card - 2 or 16 application areas 32k bit (4k Bytes) card - 16k bits in 2 or 16 application areas plus 16k bits user configurable		
<b>Write Endurance</b>	Min. 100,000 cycles		
<b>Data Retention</b>	10 years		
<b>Typical Maximum Read Range</b>	• R10 2.0-3.0" (5.0-7.6cm) • R30/RW300 2.0-3.5" (5.0-8.9cm) • R40/RW400 2.5-4.5" (6.3-11.4cm) • RK40/RWK400 3.0-4.0" (7.6-10.1 cm) Dependent upon installation conditions		
<b>Options</b>	Magnetic stripe External card numbering (inkjet or laser engraving) Vertical slot punch • Custom artwork (text or graphics)		
<b>Operates With</b>	Any reader that can read iCLASS <sup>®</sup> SE™ technology		
<b>Warranty</b>	Lifetime warranty. See complete warranty policy for details		



hidglobal.com

North America: +1 512 776 9000  
Toll Free: 1 800 237 7769  
Europe, Middle East, Africa: +44 1440 714 850  
Asia Pacific: +852 3160 9800  
Latin America: +52 55 9171 1108

© 2020 HID Global Corporation. All rights reserved. HID, the HID logo, iCLASS SE, iCLASS, Secure Identity Object and iCLASS Elite are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.