

# FARGO® HDPii Plus

<b>Print Method</b>	HDP® Retransfer: Dye Sublimation / Resin Thermal Transfer
<b>Resolution</b>	300 dpi (11.8 dots/mm) continuous tone
<b>Colors</b>	Up to 16.7 million / 256 shades per pixel
<b>Print Ribbon Options</b>	<ul style="list-style-type: none"> <li>• Full-color with resin black and inhibit panel for signature or other non-printing areas, YMCKI*, 500 prints</li> <li>• Full-color with resin black and inhibit panel for signature or other non-printing areas and heat seal panel for difficult to print surfaces, YMCIKH*, 450 prints</li> <li>• Full-color with resin black and inhibit panel for signature or other non-printing areas, YMCKIKI*, 400 prints</li> <li>• Resin black, K, 3000 prints</li> </ul>
<b>HDP Film Options</b>	<ul style="list-style-type: none"> <li>• Clear (1,500 prints)</li> <li>• Standard Holographic (500 prints)</li> <li>• Custom Holographic, special order (500 prints)</li> </ul>
<b>Print Speed**</b>	Batch Mode: <ul style="list-style-type: none"> <li>• Up to 24 seconds per card / 150 cards per hour (YMC with transfer)*</li> <li>• Up to 29 seconds per card / 124 cards per hour (YMCK with transfer)*</li> <li>• Up to 40 seconds per card / 90 cards per hour (YMCKK with transfer)*</li> <li>• Up to 48 seconds per card / 75 cards per hour (YMCKI with transfer)*</li> </ul>
<b>Accepted Standard Card Sizes</b>	CR-80 (3.370" L x 2.125" W / 85.6mm L x 54mm W)
<b>Print Area</b>	Over-the-edge on CR-80 cards
<b>Accepted Card Thickness</b>	Print only: .030" (30 mil) to .050" (50 mil) / .762mm to 1.27mm
<b>Accepted Card Types</b>	ABS, Laminated PVC, PET, PETG, proximity, smart and mag stripe cards
<b>Input Card Cartridge Capacity</b>	100 cards (.030" / .762mm)
<b>Output Hopper Card Capacity</b>	100 cards (.030" / .762mm)
<b>Reject Hopper Card Capacity</b>	15 cards (.030" / .762mm)
<b>Card Cleaning</b>	Replaceable cleaning roller (included with each print ribbon)
<b>Display</b>	User-friendly, SmartScreen™ LCD Control Panel
<b>Software Drivers</b>	Windows 8/ 7/ Vista / Server 2008 & 2003/ XP
<b>Single Wire USB 2.0 Encoding Options</b>	<ul style="list-style-type: none"> <li>• ISO Magnetic Stripe Encoding, dual high- and low-coercivity, Tracks 1, 2 and 3</li> <li>• Contactless Smart Card Encoder (HID iCLASS® and MIFARE)</li> <li>• Contact Smart Card Encoder reads from and writes to all ISO7816-1/2/3/4 memory and microprocessor smart cards (T=0, T=1) as well as synchronous cards</li> </ul>
<b>Interface</b>	USB 2.0 (high speed) and Ethernet with internal print server
<b>Operating Temperature</b>	65° to 90° F / 18° to 32° C
<b>Humidity</b>	20 - 80% non-condensing
<b>Dimensions</b>	11.50" H x 24.60" W x 9.25" D / 292mm H x 625mm W x 235mm D
<b>Weight</b>	28 lbs. / 12.8 kg
<b>Certifications</b>	UL, CE, IC, FCC Class-A, CCC, BSMI, KC, MIC
<b>Supply Voltage</b>	100-240 VAC, 3.3A
<b>Supply Frequency</b>	50 Hz / 60 Hz
<b>Warranty</b>	Printer - Three Years, Printhead - Lifetime; unlimited pass
<b>FARGO Secure Materials</b>	FARGO® Card Printer/Encoders require highly specialized media to function properly. To maximize printed card quality and durability, printhead life and printer/encoder reliability, use only HID materials. HID warranties are void, where not prohibited by law, when non-HID materials are used.
<b>Options</b>	<ul style="list-style-type: none"> <li>• Dual card input hopper</li> <li>• Smart card encoding (contact/contactless), EMV Level 1</li> <li>• Printer cleaning kit</li> <li>• Secure proprietary consumables system</li> </ul>
<b>Software</b>	FARGO Workbench diagnostic utility with Color Assist spot-color matching

\* Indicates the ribbon type and the number of ribbon panels printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, I=Inhibit, F=Fluorescing, H=Heat Seal  
 \*\* Print speed indicates an approximate print speed and is measured from the time a card drops into the output hopper to the time the next card drops into the output hopper. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is dependent on the size of the file, the CPU, amount of RAM and the amount of available resources at the time of the print.



hidglobal.com

North America: +1 512 776 9000  
 Toll Free: 1 800 237 7769  
 Europe, Middle East, Africa: +44 1440 714 850  
 Asia Pacific: +852 3160 9800  
 Latin America: +52 55 5081 1650

© 2019 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, HDP, iCLASS, Smartscreen and FARGO are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.  
 2019-02-18-fargo-hdpii-plus-printer-spec-en PLT-01315

An ASSA ABLOY Group brand

ASSA ABLOY